

Block Lab Functions Cheatsheet

Basic Helper Functions

`block_field($name, $echo = true)`

Outputs the value of the field. The optional echo is true by default.

```
block_field( 'field-name' );
```

`block_value($name)`

Returns the value of the field. Essentially the same as `block_field($name, false)`.

```
block_value( 'field-name' );
```

Config Functions

`block_config()`

Returns the block's settings.

```
block_config();
```

`block_field_config($name)`

Returns the field's settings.

```
block_field_config( 'field-name' );
```

Repeater Functions

`block_row()`

`block_rows()`

`block_sub_field()`

`block_sub_value()`

`reset_block_rows()`

These two examples do the same thing. The first uses the `block_sub_field()` function while the second echos the `block_sub_value()` function.

```
while ( block_rows( 'example-repeater-field' ) ) :
  block_row( 'example-repeater-field' );
  block_sub_field( 'example-repeater-subfield' );
endwhile;
reset_block_rows( 'example-repeater-field' );
```

```
while ( block_rows( 'example-repeater-field' ) ) :
  block_row( 'example-repeater-field' );
  echo block_sub_value( 'example-repeater-subfield' );
endwhile;
reset_block_rows( 'example-repeater-field' );
```

PHP API Functions

`block_lab_add_block()`

`block_lab_add_field()`

```
block_lab_add_block( 'example-block', array( 'icon' => 'waves' ) );  
block_lab_add_field( 'example-field-one', 'my-first-example-field' );  
block_lab_add_field( 'example-field-two', 'my-second-example-field', array( 'placeholder' => 'example' ) );
```